



F5se

System

Processor	Intel Celeron J6412 (1.5M Cache, 2.60 GHz)
Display	15" LED-backlit TFT LCD, 1024x768
Touchscreen	PCT (Projective Capacitive Touch)
Memory	1*4GB, 1*DDR4 SODIMM socket, max. 32GB
Storage	1*128GB PCIe Gen3x4 NVMe M.2 2280 SSD
TPM	Intel PTT / TPM 2.0
Speakers	2*2W
Dimensions & Weight	366 (W)* 159(D)* 302(H) mm, 6 Kgs
Operating system	Windows 10 IoT Entry, Windows 11 IoT Entry

Ports & Power

LAN port	1*RJ45 (10/100/1000 Mbps)
External display port	1
USB port	2*USB3.0, 4*USB2.0
COM port	3*RJ48
Cash drawer port	1*RJ11 (24V)
Audio port	1*3.5 mm CTIA (Line-out/Mic-In)
Power	100~240V, 50/60Hz

Environment & Certification

Operating	0~40°C, 10~90%RH
Storage	-20~60°C, 10~90%RH
Safety & IP rating	FCC/CE, IP54

Peripheral Option

Wireless Communications	802.11 a/b/g/n/ac + Bluetooth
Customer display	9.7" M9 / 10" M10 / 15" M15 (Touch Available) VFD 2x20 Line Display
Magnetic card reader	3 tracks, USB I/F
Smart card reader	ISO 7816 compatible, USB I/F
Fingerprint reader	512 dpi, 8-bit grayscale, USB I/F
iButton reader	USB I/F
1D / 2D Barcode Scanner	USB I/F
RFID reader	13.56MHz, ISO 14443A, Read/Write, USB Virtual COM I/F



Dimension (unit: mm)

