



KDS 21 II series

System	
Processor	KDS 21V II - Intel Core i3-1215U (10M Cache, up to 4.40 GHz) KDS 21H II - Intel Core i5-1235U (12M Cache, up to 4.40 GHz) KDS 21U II - Intel Core i7-1255U (12M Cache, up to 4.70 GHz)
Display	21.5" LED-backlit TFT LCD, FHD (1920x1080), 250 cd/m ²
Touchscreen	PCT (Projected Capacitive Touch)
Memory	4GB, 1*DDR4 SODIMM socket, max. 32GB
Storage	1*128GB PCIe Gen4x4 NVMe M.2 2280 SSD, 1*PCIe Gen4x4 M.2 2280 expansion socket, support RAID 0/1
TPM	Intel PTT / TPM 2.0
Speakers	2*2W
Dimensions & Weight	Product: 518.9(W)*46(D)*321.6(H) mm, 8 Kgs In Carton: 709(W)*500(D)*200(H) mm, 9.5 Kgs
Mounting	VESA 100x100 mm
Operating System	Windows 10 IoT, Windows 11 IoT
Ports & Power	
LAN port	1*RJ45 (10/100/1000 Mbps)
USB port	3*USB2.0, 1*USB3.0
COM port	2* RJ48 (RS232)
Video port	1
Cash drawer port	1* RJ12 (24V)
Built-in power adapter	Input: 100~240V, 50/60Hz Output: 19VDC, 90W
Environment & Certification	
Operating	0~40°C, 10~90%RH
Storage	-20~60°C, 10~90%RH
Safety & IP rating	FCC/CE, IP66
Peripheral Option	
Wireless LAN	802.11 a/b/g/n/ac, Bluetooth



I/O option

