

- Rugged & Connected
- Windows / Intel Architecture
- Integrated MSR, Barcode Reader, Smart Card Reader
- Docking Station



Elo Tablet

Overview

The Elo® Tablet is designed to help retailers enhance their customer experience and drive sales efficiency through a point-of-service (POS) and point-of-information (POI) platform that is portable, intuitive, reliable and secure. Millions of real-life retail installations all over the world have helped Elo develop unique insight for this next generation of our touch computing innovation.

Running Microsoft® Windows® and featuring an Intel® Atom™ processor with solid-state drive, the tablet has been purpose-built to support leading point-of-sale software environments

Professional Touch, Built for Retail

With a broad product portfolio, proven history of quality & reliability, and strong industry partnerships – Elo can help redefine how stores attract and retain customers. Elo's retail tablet directly answers the requirements of a mobile hardened store system for mobile POS, line busting, and inventory management. The Elo tablet delivers all the functionality for native POS transactions and shopper assist.

For over 40 years, with installations at more than twenty million locations around the world, Elo Touch Solutions delivers dependable retail-hardened store systems. Market leaders across

and the mobile POS (mPOS) initiatives embraced by leading retailers. This is a tablet with all the centralized management and security capabilities of the Windows environment, in a commercial form factor that reduces theft risk. An integrated magnetic stripe reader, barcode reader, removable battery and wireless printing/ networking is housed in a form factor designed to withstand being dropped. A complementary docking station provides connectivity to a broad array of peripheral interfaces while also charging the main battery and an auxiliary battery pack simultaneously.

the globe rely on Elo store technology day in and day out to facilitate critical point of sale transactions, enhance brand experiences and drive interactive omnichannel portals. Elo provides the largest portfolio of systems supporting the largest breadth of touch technologies. Rather than requiring the user to adapt to one type of touch, Elo's architecture delivers broad flexibility of acoustic, capacitive, infrared, optical, projected and resistive technology which adapts to a variety of retail environments where mobility, design style, lighting, moisture, gloves, 24/7 reliability, and ease of retail deployment can all be optimized.

PRODUCT OVERVIEW

Benefits:

Reliable

- Ruggedized to survive retail environments
- Centralized security and management
- Quality touch from a trusted retail supplier

Integrated

- MSR, Barcode Reader, and Smart Card Reader
- Designed for EMV
- Wi-Fi, Bluetooth, NFC and RFID wireless
- Docking station with battery charging location, Ethernet, 3 x USB, and VGA

Compatible

- Windows / Intel support for your existing applications
- USB connectivity to external peripherals
- Deployable in cloud, thin-client, or client-server environments

Purpose Built

- Mobile Point-of-Service
- Omnichannel Insight
- Endless Aisle

Specifications			
Model	ETT10A1 Windows Embedded 7 Standard (E806980) or Without O/S (E489570)		
Screen Size	10.1"		
Processor	Intel Atom N2600 Dual Core 1.6 GHz		
Chipset	Intel NM10		
BIOS	Phoenix		
Memory (RAM)	2GB DDR3 – 1066 MHz (not expandable beyond 2GB)		
Storage	32GB MSATA SSD		
USB Ports	1 x USB 2.0 on tablet; 3 x USB 2.0 on Docking Station		
Ethernet Port	1 x LAN RJ45 (10/100M) (when docked in Docking Station)		
Wireless	WiFi (802.11 b/g/n), Bluetooth (4.0), NFCIP-1 Reader/Writer		
Audio Ports	3.5mm audio mic/earphone hidden/protected cover		
Speakers	Internal speaker		
Operating System Options	Windows Embedded 7 Standard (Also licensed for Windows Embedded 8 Standard)		
Languages	English (default), French, German, Italian, Spanish, Simplified Chinese, Traditional Chinese		
Display	1366x768 LCD on tablet; VGA DB15 output via Docking Station		
Aspect Ratio	16:9 (wide)		
Active Display Area	222 mm x 125 mm		
Native (optimal) Resolution	1366 x 768		
Brightness (typical)	LCD Panel: 380 nits With Touchscreen: 335 nits		
Contrast Ratio (typical)	800:1		
Display Response Time (typical)	25ms		
Touch Technology	PCAP (Projected Capacitive) Multi Touch (4 touch)		
Power Adapter	AC 120/220V (50/60 Hz), 36W		
Typical Power Consumption (without peripherals)	7W - estimated battery run time up to 7 hours		
Maximum Dimensions (W x H x D)	Tablet : 11.52" x 0.79" x 8.17"	Dock : 11.5" x 7.1" x 7.8"	
Shipping Box Dimensions (W x H x D)	Tablet : 15.8" x 4.1" x 12.5"	Docking : 24.2" x 15.3" x 20.3"	
Weight	Tablet : 2.5 lbs	Docking: 2.8 lbs	
Shipping Weight	Tablet: 4.4 lbs	Docking : 4.8 lbs	
Temperature	Operating: 0°C to 40°C	Storage: -20°C to 60°C	
Humidity (non-condensing)	Operating: 20% to 80%	Storage: 5% to 95%	
Regulatory approvals and declarations	UL/cUL FCC	CE CB	UNDOT ROHS
REACH			
Mounting Options	VESA mount via optional accessory bracket (E624438)		
MTBF	50,000 hours demonstrated		
Sealing	IP54		
Rugged	Tested to MIL-STD-810G drop spec at 1 meter*		
Power Cables	North American and European power cables included		
Other Functions	Integrated Magnetic Stripe Reader (MSR) Internal/ integrated barcode reader (via rear facing auto focus camera)	Internal/ integrated Smart Card Reader Internal Webcam (Front facing AF Camera) European Mastercard VISA (EMV) Ready	
Optional Accessories	VESA Bracket (E624438) Docking Station (E518363) Stylus (E761200) Additional Battery (E840851)	Replacement Dock Cover (E108413) Replacement Hand Strap (E697779) Replacement Power Supply (E452058)	